

# TITANIUM DIOXIDE

T e c h n i c a l   D a t a

# CR-826S

TRONOX® CR-826S is the water-based slurry version of CR-826 that combines very high durability, gloss retention and chalk resistance in exterior applications with excellent optical properties. The combination of high tint strength and excellent durability make this product an excellent choice for both interior and exterior water-based architectural coatings.

## Applications

- Recommended for interior and exterior water-based architectural coatings

## Typical Properties<sup>1</sup>

Solids (%)	76.5
Density, lbs/gal	19.6
pH	8.5
Viscosity, cps @ 100 rpm <sup>2</sup>	125
Volatile	Water

## Production Locations

Hamilton, Mississippi, U.S.

**TRONOX**

<sup>1</sup>Typical properties not to be construed as specifications

<sup>2</sup>Brookfield RVT II

The information herein is believed to be reliable. However, no warranty, expressed or implied, is made as to its accuracy or completeness and none is made as to the merchantability of the material or its fitness for any purpose. The manufacturer shall not be liable for consequential damages or for damages to persons or property resulting from its use. Nothing herein shall be construed as a recommendation for use in violation of any patent.

### Plant Locations:

Botlek, Netherlands  
Hamilton, Mississippi, U.S.  
Kwinana, Australia  
Savannah, Georgia, U.S.  
Uerdingen, Germany

### Sales Offices:

Oklahoma City 1-800-654-3911  
Singapore 65-6255-0098  
Uerdingen 49-2151-88-8188