



## Technical Data Sheet

# Tronox<sup>®</sup> 8141SL

TRONOX<sup>®</sup> 8141SL is the slurry form of TRONOX<sup>®</sup> 8140. The highly treated rutile titanium dioxide pigment designed to provide the optimum opacity and tint strength in quality high-PVC architectural coatings. Its slurry form has preserved the high dry hiding, tint strength, and brightness as well as the clean tint tone and color of the pigment.

### Applications

Flat architectural coatings ■ Water based ■ 50% PVC & higher

### Typical Properties<sup>1</sup>

Solids content, % .....	64.5
Density, lbs/gal .....	15.6
pH .....	8.8
Viscosity, cps <sup>2</sup> .....	180
Volatile .....	Water

<sup>1</sup>Typical properties not to be construed as specifications

<sup>2</sup>Brookfield, @ 100 rpm

### Plant Locations:

Botlek, The Netherlands  
Mississippi, U.S  
Kwinana, Australia

### Sales Offices:

Oklahoma City 1 800 654 3911  
Singapore +65 6255 0098  
Shanghai, China +86-21-6422-8955  
Perth, Australia +61 8 9411-1444  
Botlek, The Netherlands +31 181 246600

06/17

The information herein is believed to be reliable. However, no warranty, expressed or implied, is made as to its accuracy or completeness and none is made as to the merchantability of the material or its fitness for any purpose. The manufacturer shall not be liable for consequential damages or for damages to persons or property resulting from its use. Nothing herein shall be construed as a recommendation for use in violation of any patent.